

Press Release

FOR IMMEDIATE RELEASE

August 11, 2008

Model L101 TRMS Current Data Logger

The Simple Logger[®] II TRMS Current Data Logger is a cost effective, advanced designed product incorporating features and functions not found in Data Loggers costing 2 to 3 times its price. The choice of data storage modes and storage rates allows the operator to effortlessly configure these loggers to optimize memory usage to the application at hand. Extended Recording Mode (XRM[®]) and delayed start time are just two of the many application friendly features in these loggers.

An internal memory allows storing over 240,000 measurements, more than enough for most data collection needs. The Simple Logger[®] II Model L101 records True RMS AC Current at user selectable rates from 8 every second to 1 every day. Currents can be measured and recorded with 0.1A resolution. Battery operation and compact size allows for installation in tight locations without the need for external power. A series of front panel LEDs provides a quick status the logger's state and memory usage.

DataView[®], the comprehensive application software, included free, facilitates real-time viewing of measurement data even while recording. Instrument configuration, data storage and report generation from pre-defined templates or operator custom designed templates are also standard features. Several Data Loggers can be synchronized to record at the same time intervals via the DataView[®] software, as well.

Submitted by:

Kathleen Annis, Marketing Communications Manager
AEMC[®] Instruments
200 Foxborough Blvd.
Foxborough, MA 02035-2872
(508) 698-2115
(508) 698-2118 (fax)
kannis@aemc.com

Technical Contact:

Bud Myers, Technical Engineer
techsupport@aemc.com



Applications:

- Fault current detection
- Intermittent problem detection
- Harmonic Current recording using DataView[®] software
- Load profiling
- Neutral Current monitoring
- Metering CT resizing
- Demand recording