

Product Options for VTM4140PKG

VTM Series Packages	3 Gb/s Input	HD/SD-SDI Input	RGB Dual Link	SD-SDI Input	Analog Composite Input	ASI Input	Standard Inputs	Optional Inputs/Optional Input Modules	Looping SDI Inputs	Looping Analog Inputs	Multi-input Q-SEE Display Capability	Looping Inputs Type	Eye Pattern	Jitter Waveform	Jitter Spectrum	Waveform	Vector	Gamut	Pixel Locator/Data Word Analyzer	Line Select	Relative Timing	Closed Caption	Alarm Log	Audio	Remote Mgt via LAN Port	USB Port	Remote Control Panel	XGA/DVI Display Connector	Size # of Rack Units
VTM4140PKG	OP	•	OP	OP	OP	OP	2	2/1	•		•	Passive	OP	OP	OP	•	•	•	•	•	•	•	•	OP	•	•	OP	•	1
VTM4140PKG-A	OP	OP		OP	•	OP	2	2/1		•	•	Passive	OP	OP	OP	•	•	•		•	•	•	•	OP	•	•	OP	•	1
VTM4140PKG-SD	OP	OP		•	OP	OP	2	2/1	•		•	Passive	OP	OP	OP	•	•	•	•	•	•	•	•	OP	•	•	OP	•	1
VTM4140PKG-EH	OP	•	OP	OP	OP	OP	2	2/1	•		•	Active	•			•	•	•	•	•	•	•	•	OP	•	•	OP	•	1
VTM4140PKG-EJ	OP	•	OP	OP	OP	OP	2	2/1	•		•	Active	•	•	•	•	•	•	•	•	•	•	•	OP	•	•	OP	•	1
VTM4140PKG-ES	OP		OP	•	OP	OP	2	2/1	•		•	Active	•			•	•	•	•	•	•	•	•	OP	•	•	OP	•	1
VTM4140PKG-3GB	•	OP	•	OP	OP	OP	2	2/1	•		•	Active	OP	OP	OP	•	•	•	•	•	•	•	•	OP	•	•	OP	•	1
Name for option or upgrade TVM-VTM-xxx	3GB	SDI- H	DLK	SDI-S	AVC-2	ASI							JEM/ EYE-x [‡]	JEM	JEM									A ³ -xx [†]					

- Supported feature
- OP Product option; only one input module option allowed
- Empty box; product option is not available
- † A3xx See advanced audio options table for more details
- ‡ EYE-x where x = H for HD/SD; x = S for SD



205 Westwood Ave
Long Branch, NJ 07740
1-877-742-TEST (8378)
Fax: (732) 222-7088
salesteam@Tequipment.NET